

# AKTİF KARBON FİLTRASYON SİSTEMLERİ

## VALFLİ AKTİF KARBON FİLTRE SİSTEMLERİ

FİLTRASYON SİSTEMLERİ

2022



UZ - AR  
MÜHENDİSLİK



## VALFLİ AKTİF KARBON FİLTRE SİSTEMLERİ

MODEL	TANK BOYUT	CİHAZ BAĞLANTI ÇAPI	SERVİS DEBİSİ m3/saat		MİNERALLER	
			Hız = 20 m/saat	Max Hız = 30 m/saat	KARBON (kg)	QUARTZ (kg)
C - 8	8" x 17"	1"	0,65	0,97	4	---
C - 15	7" x 35"	1"	0,5	0,74	7	---
C - 20	8" x 35"	1"	0,65	0,97	9	---
C - 25	9" x 35"	1"	0,82	1,23	12,5	---
C - 30	10" x 35"	1"	1,01	1,52	15	---
C - 50	10" x 54"	1"	1,01	1,52	25	---
C - 60	12" x 48"	1"	1,46	2,19	30	10
C - 80	13" x 54"	1"	1,71	2,57	35	15
C - 100	14" x 65"	1"	2,59	2,98	45	15
C - 150	16" x 65"	1"	2,59	3,89	65	20
C - 200	18" x 65"	1"	3,28	4,92	80	25
C - 250	21" x 62"	1"	4,47	6	100	50
C - 50	10" x 54"	1 1/4"	1,01	1,52	25	---
C - 60	12" x 48"	1 1/4"	1,46	2,19	30	10
C - 80	13" x 54"	1 1/4"	1,71	2,57	35	15
C - 100	14" x 65"	1 1/4"	1,98	2,98	45	15
C - 150	16" x 65"	1 1/4"	2,59	3,89	65	20
C - 200	18" x 65"	1 1/4"	3,28	4,92	80	25
C - 250	21" x 62"	1 1/4"	4,47	6,7	100	50
C - 100	14" x 65"	1 1/2"	1,98	2,98	45	25
C - 150	16" x 65"	1 1/2"	2,59	3,89	65	50
C - 200	18" x 65"	1 1/2"	3,28	4,92	80	50
C - 250	21" x 62"	1 1/2"	4,47	6,7	100	75
C - 300	24" x 72"	1 1/2"	5,83	8,75	125	100
C - 500	30" x 72"	1 1/2"	9,12	13,62	150	225
C - 300	24" x 72"	2"	5,83	8,75	125	100
C - 500	30" x 72"	2"	9,12	13,67	150	225
C - 750	36" x 72"	2"	13,13	19,69	225	325

\*Valflerin zaman ayarlı veya volumetrik çeşitleri mevcuttur. Tank büyüklükleri ve valflerin bağlantı çapları Sistemlerde kullanılan valf markaları: Clack, Fobrite, Fleck, Runxin, Autotrol