

SU YUMUŐATMA SİSTEMLERİ

VALFLİ VOLÜMETRİK KONTROLLÜ YUMUŐATMA SİSTEMLERİ

FİLTASYON SİSTEMLERİ

2022



UZ - AR
MÜHENDİSLİK



VALFLİ VOLÜMETRİK KONTROLLÜ YUMUŞATMA SİSTEMLERİ

MODEL	TANK BOYUT	CİHAZ BAĞLANTI ÇAPLI	SERVİS DEBİSİ m ³ /saat	MİNERAL REÇİNE (lt)
			Max Hız = 40 m ³ /m ³ -reçine.saat	
SC - 8	8" x 17"	1"	0,32	8
SC - 15	7" x 35"	1"	0,6	15
SC - 20	8" x 35"	1"	0,8	20
SC - 25	9" x 35"	1"	1	25
SC - 30	10" x 35"	1"	1,2	30
SC - 8	8" x 17"	1"	0,32	8
SC - 15	7" x 35"	1"	0,6	15
SC - 20	8" x 35"	1"	0,8	20
SC - 25	9" x 35"	1"	1	25
SC - 30	10" x 35"	1"	1,2	30
S - 8	8" x 17"	1"	0,32	8
S - 15	7" x 35"	1"	0,6	15
S - 20	8" x 35"	1"	0,8	20
S - 25	9" x 35"	1"	1	25
S - 30	10" x 35"	1"	1,2	30
S - 50	10" x 54"	1"	2	50
S - 60	12" x 48"	1"	2,4	60
S - 80	13" x 54"	1"	3,2	80
S - 100	14" x 65"	1"	4	100
S - 150	16" x 65"	1"	6	150
S - 200	18" x 65"	1"	6,1	200
S - 250	21" x 62"	1"	6,1	250
S - 50	10" x 54"	1 1/4"	2	50
S - 60	12" x 48"	1 1/4"	2,4	60
S - 80	13" x 54"	1 1/4"	3,2	80
S - 100	14" x 65"	1 1/4"	4	100
S - 150	16" x 65"	1 1/4"	6	150
S - 200	18" x 65"	1 1/4"	7,7	200
S - 250	21" x 62"	1 1/4"	7,7	250
S - 100	14" x 65"	1 1/2"	4	100
S - 150	16" x 65"	1 1/2"	6	150
S - 200	18" x 65"	1 1/2"	8	200
S - 250	21" x 62"	1 1/2"	10	250
S - 300	24" x 72"	1 1/2"	12	300
S - 200	18" x 65"	2"	8	200
S - 250	21" x 62"	2"	10	250
S - 300	24" x 72"	2"	12	300
S - 500	30" x 72"	2"	20	500
S - 750	36" x 72"	2"	26	750
S - 900	42" x 72"	2"	26	900

*Valflerin zaman ayarlı veya volumetrik çeşitleri mevcuttur. Tank büyüklükleri ve valflerin bağlantı çapları proje sistemlerde kullanılan valf markaları: Clack, Fobrite, Fleck, Runxin, Autotrol